

Guangzhou Clean-link Filtration Technology Co.,Ltd

Add: No. 36, Jianshe South Road, Conghua District, Guangzhou, Guangdong Province, China Tel: +86-020-87469992/87469993/87468869 Fax: +86-020-87469985 E-mail: rita@clean-link.cn info@clean-link.cn

Pre Efficiency Pocket Filter

FILTRATION GRADE G3 G4 M5









PRODUCT FEATURES

- ▶ The filter material is processed by high performance hot melt method composed of anti-fracture organic synthetic fiber. The reinforced structure has good filtration performance and large dust capacity.
- ▶ Each group of bags has a positioning air duct to ensure the best filtration effect.
- ▶ The filter bag adopts line seam technology.
- ▶ Strong moisture resistance ,100% moisture resistance.

USING

▶ Painting industry painting workshop front filtration, air conditioning ventilation system filtration, filtration system pre-filtration, high-efficiency filter pre-filtration.

TECHNICAL DATA

Filtration Grade	Dimensions (mm) W x H x D	Number of Bags	Filtration Area (㎡)	Rated Air Flow (m³/h)	Initial Pressure Drop (Pa)	Final Pressure Drop (Pa)
G3	287 x 595 x 550	3	1.92	1700	30	200
	495 x 595 x 550	5	3.28	2600	30	200
	595 x 595 x 600	6	4.05	3400	30	200
G4	287 x 595 x 550	3	1.92	1700	45	250
	495 x 595 x 550	5	3.28	2600	45	250
	595 x 595 x 600	6	4.05	3400	45	250

★ Data may change without notice. Other specifications and thickness are available on request.





