CLEAN-LINK®
PROFESSIONAL FILTRATION SOLUTIONS

Guangzhou Clean-link Filtration Technology Co.,Ltd
Add: No. 36, Jianshe South Road,Conghua District, Guangzhou, Guangdong Province, China
Tel: +86-020-87469992/87469993/87468869 Fax: +86-020-87469985
E-mail: rita@clean-link.cn info@clean-link.cn

FFU (Fan Filter Unit)

PRODUCT FEATURES

- The FFU box made of cold-rolled steel plate sprayed plastic or stainless steel has a strong structure.
- Direct-drive high-efficiency centrifugal fan is adopted, which has long life, low noise, maintenance-free, low vibration and adjustable speed.
- It is suitable for assembling into an ultra-clean production line, which can be used as a single unit according to the process layout, or multiple units can be connected in series to form a 100-stage assembly line.

TECHNICAL DATA

Box Size (mm) W x H x D	575 x 575 x 290	1175 x 575 x 290	1175 x 875 x 290	1175 x 1175 x 290
Keel Size (mm)	600 x 600	600 x 1200	900 x 1200	1200 x 1200
Air Flow (CMM)	5 ~ 8	12 ~ 18	19 ~ 28	21 ~ 37
Wind Velocity Test (m/s)	0.45±20%			
HEPA Efficiency	⩾99.95 - 99.995@MPPS			
HEPA Size	570 x 570 x 70	1170 x 570 x 70	1170 x 870 x 70	1170 x 1170 x 70
Noise	48 - 54dB (A)	48 - 54dB (A)	50 - 56dB (A)	52 - 58dB (A)
Shell Material	Galvanize / Aluminium / Stainless steel			
Power Supply	AC Single-phase : 110V / 220V / 50Hz / 60Hz			
Power (w)	130 - 150	130 - 150	170 - 190	235 - 255

★ Data may change without notice. Other specifications and thickness are available on request.

CLEAN-LINK®
PROFESSIONAL FILTRATION SOLUTIONS

Guangzhou Clean-link Filtration Technology Co.,Ltd
Add: No. 36, Jianshe South Road,Conghua District, Guangzhou, Guangdong Province, China
Tel: +86-020-87469992/87469993/87468869 Fax: +86-020-87469985
E-mail: rita@clean-link.cn info@clean-link.cn

FFU (Fan Filter Unit)

PRODUCT FEATURES

- Use stainless steel or paint cold-rolled board.
- Light weight, easy to install and maintain.
- Low energy consumption, low noise, high static pressure.
- Adjustable wind speed operation, uniform wind speed.

TECHNICAL DATA

Dimensions (mm) W x H x D	**Output Power** (W)	**Rated Air Flow** (m^3/h)	**Filtration Efficiency** (0.3μm)
615 x 615 x 320	80~160	600	⩾99.95 - 99.995@MPPS
915 x 615 x 320	80~160	900	
1175 x 575 x 320	80~160	1000	
1225 x 615 x 320	80~160	1200	
1175 x 1175 x 320	160~320	2000	